### LEADWAY

# TS-828 龍門移動式油壓裁斷機 HYDRAULIC DYNAMIC TRAVELING HEAD CUTTING MACHINE

#### Application 功能:

This machine is suitable for plastic, leather, foam, nylon, fabric, cardboard, and various synthetic materials, one or several layers of forming and cutting. Such as leather processing industry, garment industry, footwear industry, leather bag industry, toy industry and automobile industry are applicable.

此機適用於塑膠、皮革、泡棉、尼龍、布料、紙板、及各種合成材料,一層或數層的成型裁斷。如皮革加工業、成衣業、製鞋業、皮包業、玩具業及汽車工業均適用。



#### Feature 特色:

- The movement of travelling head is controlled by two-hand and an automatic travelling switch to make operation easily. 裁斷頭的左右位移迅速,採 用雙手操作及自動位移 開關控制,操作方便。
- Two-hand operation and no continuous cutting are designed for security.

採雙手操作,無連續多次裁切的動作,安全性高。

 The structure of travelling head provides good operating view for easy operation.

此機台為龍門形式的機械架構,操作視線佳。

- The cutting stroke can be adjusted easily and quickly in accordance with the height of cutting dies. 裁切 高度容易,可迅速配合刀具的高度迅速調整。
- High capacity and Low power consumption.
   高產能、低耗能。
- The roller feeding system or rear material plate is available.

可加裝後製料盤或滾輪送料裝置。

#### Specification 規格表:

機型 Model	TS-828	
工作臺尺寸 Cutting Force	25tons	
有效裁斷面積 Hydraulic Motor Power	2 HP	
壓 力 Positional Motor Power	1 HP	
馬 達 Cutting Head	500 x 500 mm	
速度 Cutting Pad	1600 x 500 mm	
壓盤上下行程 Stroke	5 – 120 mm	
機械尺寸 Oil Filling	60 L	
機械尺寸 Machine Size	195*128*199 cm	

# LEADWAY

# TS-829 平面式油壓裁斷機 HYDRAULIC PLANE CUTTING MACHINE

#### Application 功能:

This machine is suitable for one layer or multiple layers cutting for plastic, leather, foam, nylon, fabric, cardboard and other synthetic materials. 20T or 25T cutting pressure are available. According to the shortcomings of the traditional mechanical , this advanced design improved the production efficiency and easy operation.

本機適用於塑膠、皮革、泡棉、尼龍、布料、紙板、 及各種合成材料、一層或數層的成形裁斷。具 20 或 25 噸裁斷壓力,動作輕巧迅速,是針對傳統機械式 裁斷機的缺點加以改進設計,提高業界生產效率。



#### Feature 特色:

- Save labor, easy operation, low trouble rates, strong cutting force and fast cutting speed (above 1,000 times/hour). 操作省力、簡單、故障率低,裁斷力強,裁斷速度快,每小時可達 1,000 刀次以上。
- Cutter setting, installation, cutting stroke adjustments are very easy, accurate and quick.
   刀模設定裝置,高低刀模調整,非常簡單、準確、快速。
- Quiet operation to greatly reduce the noise level in the workshop, safe work environment and increase production efficiency. 作業時寂靜,可大量降低工廠噪音,改進工作環境,提高工作效率。
- The fine-tuning device can easily obtain the best cutting stroke and prolong the service life of the cutting dies and the cutting board. 微調裝置,可輕易得到最佳裁斷衝程,延長刀模及裁斷板使用壽命。

#### Specification 規格表:

機型 Model	TS-829	
工作壓力 Pressure	20 tons	25 tons
衝程 Stroke	10mm-100mm	10mm-100mm
裁斷面積 Cutting Area	410 x 1250 mm	460 x 1600 mm
馬力 Horsepower	2 HP x 4P	3 HP x 4P
淨重 N.W.	1180 Kgs	1400 Kgs
機械尺寸 Machine Size	1480x800x1430 mm	1830x800x1430 mm

# LEADWAY

#### TS-829A 搖臂式裁斷機

#### HIGH SPEED HYDRAULIC CUTTING MACHINE


#### Application 功能:

This machine is suitable for one layer or multiple layers cutting for plastic, leather, foam, nylon, fabric, cardboard and other synthetic materials.

本機適用於塑膠、皮革、泡棉、尼龍、布料、紙板、及各種 合成材料、一層或數層的成形裁斷。

#### Feature 特色:

- Save labor, easy operation, low trouble rates, strong cutting force and fast cutting speed and easy to maintain.
   操作省力、簡單、故障率低,裁斷力強,裁斷速度快,保養容易。
- Cutter setting, installation, cutting stroke adjustments
   are very easy, accurate and quick.
   刀樹鉛完裝署,享低刀樹調敷,非骨簡買、進確、快速



● The automatic lubrication system lubricates each parts to prolong service life. 具油壓自動潤滑系統,自動潤滑各機件,延長壽命。

#### Specification 規格表:

機型 Model	TS-829A	
工作壓力 Pressure	20 tons	25 tons
衝程 Stroke	25mm-115mm	25mm-115mm
裁斷面積 Cutting Area	900 x 430 mm	1000 x 500 mm
馬力 Horsepower	2 HP x 4P	2 HP x 4P
搖臂寬度 Arm Width	370 mm	500 mm
淨重 N.W.	1062 Kgs	1202 Kgs
機械尺寸 Machine Size	1000x900x1450 mm	1050x1000x1450 mm

